

CSMA Shared Non Protected Frequencies & Guidelines

CSMA has provisions for shared non protected frequency pairs (SNP). These SNP frequencies are not intended for permanent coordinated systems. The SNP frequency pairs are intended for temporary use not to exceed 30 days at any one location.

Guidelines for SNP usage:

- Not intended for coordinated systems
- Temporary, Portable or Special Events use
- Not to exceed 30 days of continued operation at any one location
- Not to exceed 50 watts ERP
- Shall utilize access control on the repeater receiver (PL, DPL, CC)
- Shall cease operations if notified of interference to coordinated systems
- Shall adhere to all FCC rules & regulations and utilize good engineering practices
- Shall notify CSMA of intended operations as soon as possible. Please supply the below information upon notifying CSMA via email. <mailto:coord@ctspectrum.com>

- (1) Intended dates of operation
- (2) Location of intended use
- (3) Frequency pair(s) to be utilized
- (4) Access control mode(s) (PL, DPL Tone or Color Code)
- (5) Mode of operation (Analog, Digital)
- (6) Contact information

Frequency pairs available for SNP use:

	Output	Input
50 MHz	53.570	52.570
144 MHz	145.430	144.830
220 MHz	224.440	222.840
440 MHz	442.000	447.000